

One touch and off it goes ...



QUICKCHECK *webline*®

Portable Constancy
Check Device

PTW

Completely Automatic Measurement

Set one time, use day after day:

Complete LINAC QA in an automated measurement procedure – simple, compact and wireless.



► Checks dose, dose rate, homogeneity, symmetry, beam quality,

Routine and Time-Saving LINAC QA

FFF Compensator (X6, X10) available

to perform LINAC QA of FFF beams just as you are used to it.



QUICKCHECK *webline* ®

- ▶ Intuitive operability
- ▶ Ready for use immediately every day
- ▶ Track-it data management

dynamic and static wedges according to pre-defined task lists ▶

SET ONE TIME, USE DAY AFTER DAY

A task list is created for each linear accelerator in radiotherapy using the **WorklistGenerator**: The software makes it possible to define all relevant test parameters for comprehensive quality control of accelerators and apply them in a constant, completely automatic measurement routine. The task lists are transmitted to the measurement equipment and stored there. Thereafter, QUICKCHECK^{webline} is ready for daily constancy checks without the need of additional settings.

1. Aligning and irradiating


QUICKCHECK^{webline} is placed under the linear accelerator with little work and aligned using the room laser with help of engraved lines. Thanks to a convenient auto-start and auto-stop function, one measurement after another can be performed without further intervention. For example, you can irradiate various photon and electron energies one after another. The data are stored in the device.

2. Displaying and evaluating

The task list for the respective linear accelerator is worked through completely, and the corresponding test status is calculated automatically. QUICKCHECK^{live} displays instantially the measurement results. Measurement tasks can be skipped or repeated directly from outside the treatment room. QUICKCHECK^{webline} manages task lists for any number of accelerators; all available LINACS can be checked with only one measurement device, and the measurement values of several months can be stored in the device.

3. Analyzing and archiving

The data stored in QUICKCHECK^{webline} can be transferred to a PC via RS232, USB or LAN at any time. QUICKCHECK software supports fast long-term analysis. Data transfer to Track-it offers to manage all QA data on one single platform and to share it fast and effectively across your organization. Track-it features automated completion of reports by using predefined or custom protocol templates, e.g., AAPM TG-142 Daily QA. An optional QUICKCHECK^{webline} docking station, which can also be mounted on the wall, serves for data transmission as well as for charging the batteries.



Robust ionization chambers



Suitable for field sizes from 10 x 10 cm²

Specifications

Product:	Test device for constancy check of medical linear accelerators	Field sizes:	(10 x 10) cm ² , (20 x 20) cm ²
Detector type:	Vented ionization chambers, air density compensated	Temperature range:	(10 ... 40) °C, (50 ... 95) °F
Number of detectors:	13	Humidity range:	(10 ... 80) %, max. 20 g/m ³
Measured quantities:	Dose, dose rate, irradiation time, temperature and air pressure	Air pressure range:	(540 ... 1060) hPa
Nominal useful energy range:	(4 ... 25) MV photons (4 ... 10) MV photons with FFF Compensator (4 ... 25) MeV electrons	Display:	TFT color display 70 mm x 53 mm
Nominal range of dose rate:	(0.5 ... 10) Gy/min (1 ... 25) Gy/min with FFF Compensator	Interfaces:	RS232, USB und LAN (TCP/IP)
Response:	3.4 nC/Gy (typical)	Power supply:	4 rechargeable batteries AA (NiMH)
Measurement volume:	0.1/0.2 cm ³ per chamber	Outer dimensions:	380 mm x 254 mm x 67 mm, 262 mm x 262 mm x 37.5 mm Compensator X6, 262 mm x 262 mm x 58.5 mm Compensator X10
		Weight:	Measurement device 5.5 kg, Docking station 1.7 kg, Compensator X6 2.1 kg, Compensator X10 2.9 kg

ALIGNING AND IRRADIATING



and 20 x 20 cm²



Integrated energy check for photons and electrons



User-

Easy to operate

- ▶ Compact format and slight weight
- ▶ Detectors and display in one device
- ▶ Automatic air density correction
- ▶ Wireless operation
- ▶ Suitable gantry holding device available for measurements under various gantry angles

2 DISPLAYING AND EVALUATING



defined check parameters




Comprehensive network capability with USB, RS232 and LAN

Completely automatic and convenient

- ▶ Task lists defined once in advance
- ▶ Trigger-controlled measurement procedure with auto-start, auto-stop, auto-standby and auto-shutdown
- ▶ Immediate display of measurement results
- ▶ Skip or repeat measurement tasks from outside the treatment room

ANALYZING AND ARCHIVING



interfaces for PC or network connection



Data management with Track-it

Versatile and transparent

- ▶ Individually configurable evaluation
- ▶ Export analyzed data from your QUICKCHECK^{weblite} to Track-it with the click of a single button
- ▶ View and manage all your QA reports in the Track-it Dashboard
- ▶ Access QA data from multiple sources and sites with a standard web browser

Dosimetry Pioneers since 1922.

PTW is a global market leader for dosimetry and quality control solutions in radiation medicine, serving the needs of medical radiation experts in more than 160 countries worldwide. Starting with the famous Hammer dosemeter in 1922, the German manufacturer is one of the pioneers in medical radiation measurement, known for its unparalleled quality and precision.

For PTW, making medical radiation safer is both a passion and lifetime commitment. The family-run high-tech company operates one of the oldest and largest accredited calibration laboratories in the field of ionizing radiation and established THE DOSIMETRY SCHOOL to promote the exchange of knowledge in clinical dosimetry.

For more information on PTW products visit www.ptw.de or contact your local PTW representative:

Headquarters

PTW-Freiburg
Physikalisch-Technische Werkstätten
Dr. Pychlau GmbH
Lörracher Straße 7
79115 Freiburg · Germany
Phone +49 761 49055-0
Fax +49 761 49055-70
info@ptw.de
www.ptw.de

PTW Dosimetria Iberia S.L.
Calle Profesor Beltrán Báguena nº 4 - 312E
46009 Valencia · Spain
Phone +34 96 346 2854
Fax +34 96 321 2140
info@ptwdi.es
www.ptwdi.es

PTW-Asia Pacific Ltd.
Workshop I on 11th Floor
Valiant Industrial Centre
Nos. 2-12 Au Pui Wan Street
Fo Tan, New Territories · Hong Kong
Phone +852 2369 9234
Fax +852 2369 9235
info@ptw-asiapacific.com
www.ptw-asiapacific.com

PTW-UK Ltd.
Old School House
Station Road East
Grantham Lincolnshire
NG31 6HX · United Kingdom
Phone: (+44) 1476 577503
Fax: (+44) 1476 577503
sales@ptw-uk.com
www.ptw-uk.com

PTW-New York Corporation
140 58th Street
Suite # 5H3
Brooklyn, New York 11220 · USA
Phone (1-516) 827 3181
Fax (1-516) 827 3184
ptw@ptwny.com
www.ptwny.com

PTW-Beijing Ltd
Room 712, JinYiYe Building
No. 2 Sheng Gu Zhong Lu
ChaoYang District
100029 Beijing · P.R. of China
Phone +86 10 6443 0746
Fax +86 10 6442 7804
info@ptw-beijing.com
www.ptw-beijing.com

PTW-France SARL
41 Chemin de la Ceresaie
91620 La Ville du Bois · France
Phone +33 1 64 49 98 58
Fax +33 1 69 01 59 32
info@ptw-france.com
www.ptw-france.com

PTW-Latin America
Av. Evandro Lins e Silva
840 Sala 2018 · Barra da Tijuca
22631-470 Rio de Janeiro-RJ · Brazil
Phone +55 21 2178 2188
Fax +55 21 2429 6234
info@ptw.com.br
www.ptw.com.br

PTW Dosimetry India Pvt. Ltd.
ACE Towers, 2nd Floor
73/75 Dr Radhakrishnan Road · Mylapore
Chennai 600004 · India
Phone +91 44 42079999
Fax +91 44 42072299
info@ptw-india.in
www.ptw-india.in