

How to Update the QUICKCHECK ^{webline} Firmware

NOTE

This technical note describes how to update the firmware of your QUICKCHECK ^{webline}. PTW recommends downloading the saved measurement data from your QUICKCHECK ^{webline} to your PC before performing the update to the new firmware version.

- 1. Disconnect the power cable from your QUICKCHECK webline.
- 2. Make sure the device is turned off.
- 3. Connect the QUICKCHECK ^{webline} to your PC via RS232.
- 4. Start the QUICKCHECKwebline Updater on your PC.
- 5. Reconnect the power cable to your QUICKCHECK webline.
- 6. A message is displayed in the *QUICKCHECKwebline Updater* window, informing you that a connection to the QUICKCHECK ^{webline} has been established:

TW QUICKCHE Device:	CKwebline Updater V1.10 QUICKCHECKwebline	×
New Firmware:	1.5.1	
COM port:	COM1	
Connecti	on to QUICKCHECKwebline established.	
	<u> </u>	

If the message is not displayed, try selecting a different COM port. Disconnect the power cable and turn off the QUICKCHECK ^{webline}. Make sure the RS232 connection between your PC and the device is established. Reconnect the power cable.

- 7. Click *OK*.
- 8. A new message is displayed in the *QUICKCHECKwebline Updater* window, informing you that the update procedure is irreversible. Confirm that you wish to start the updating process by clicking the *Start update* button.



- 9. The QUICKCHECK ^{webline} firmware will be updated. Do not close the **QUICKCHECKwebline Updater** window.
- 10.Once the update is complete, the message *Update successful* is displayed in the *QUICKCHECKwebline Updater* window.



11.Click the *Finish* button to close the window. Your QUICKCHECK ^{webline} firmware has been successfully updated.

PTW-Freiburg Lörracher Straße 7 • 79115 Freiburg • Germany Phone +49 761 49055-0 • Fax +49 761 49055-70 info@ptw.de • www.ptw.de